

BEEPROG Universal programmer Manual

Short description:

- --33901 supported devices by 2.42 version of SW (13. Sep. 2007)
- --extremely fast programming, one of the fastest programmers in this category. Programs 16-Mbit Flash memory less than 18 seconds
- --48-pins powerful pindrivers, no adapter required for any DIL devices
- --connector for in-circuit programming (ISP)
- --dual connection to PC: USB or parallel (printer) port
- --USB 2.0/1.1 compatible interface
- --alternatively high-speed IEEE 1284 (ECP/EPP) printer-port (LPT) interface
- --comfortable and easy to use control program, Windows 95/98/Me/NT/2000/XP/2003/XPx64 compatible
- --Multiprogramming possible by attaching more programmers to one PC
- --warranty - 3 years

Optional accessories:

- --socket converters
- --Diagnostic POD for ISP connector

Features:

GENERAL

- --First member of new USB-compatible generation of Windows 95/98/ME/NT/2000/XP/2003/XP64 based ELNEC universal programmers built to meet the strong demand of the developers community for the fast and reliable universal programmer.
- --Supports all kinds of types and silicon technologies of today and tomorrow programmable devices without family-specific module. You have freedom to choose the optimal device for your design. Using built-in in-circuit serial programming (ISP) connector, the programmer is able to program ISP capable chips in circuit.
- --BeeProg isn't only a programmer, but also a tester of TTL/CMOS logic ICs and memories. Furthermore, it allows generation of user-definable test pattern sequences.
- --Provides very competitive price coupled with excellent hardware design for reliable programming. Probably best "value for money" programmer in this class.

-
- Very fast programming due to high-speed FPGA driven hardware and execution of time-critical routines inside of the programmer. At least fast than competitors in this category, for many chips much faster than most competitors. As a result, when used in production this one-socket-programmer waits for an operator, and not the other way round.
 - --BeeProg interfaces with the IBM PC 486 compatible or higher, portable or desktop personal computers through USB (2.0/1.1) port or any standard parallel (printer) port. Programmer also supports IEEE1284 (ECP/EPP) high-speed parallel port. Support of both USB/LPT port connection gives you the choice to connect the BeeProg programmer to any PC, from latest notebook to older desktop without USB port.

HARDWARE:

- --FPGA based totally reconfigurable 48 powerful TTL pindrivers provide H/L/pull_up/pull_down and read capability for each pin of socket. Advanced pindrivers incorporate high-quality high-speed circuitry to deliver signals without overshoot or ground bounce for all supported devices. Pin drivers operate down to 1.8V so you'll be ready to program the full range of today's advanced low-voltage devices.
 - --The programmer performs device insertion test (wrong or backward position) and contact check (poor contact pin-to-socket) before it programs each device. These capabilities, supported by overcurrent protection and signature-byte check help prevent chip damage due to operator error.
 - --The selftest capability allow to run diagnostic part of software to thoroughly check the health of the programmer.
 - --Built-in protection circuits eliminate damage of programmer and/or programmed device due to environment or operator failure. All the inputs of the BeeProg programmer, including the ZIF socket, connection to PC and power supply input, are protected against ESD up to 15kV.
 - --BeeProg programmer performs programming verification at the marginal level of supply voltage, which, obviously, improves programming yield, and guarantees long data retention.
 - --Various socket converters are available to handle device in PLCC, SOIC, PSOP, SSOP, TSOP, TSSOP, TQFP, QFN (MLF), SDIP, BGA and other packages.
- + -

SOFTWARE

-
- --Programmer is driven by an easy-to-use control program with pull-down menu, hot keys and on-line help. Selecting of device is performed by its class, by manufacturer or simply by typing a fragment of vendor name and/or part number.
 - --Standard device-related commands (read, blank check, program, verify, erase) are boosted by some test functions (insertion test, signature-byte check), and some special functions (autoincrement, production mode - start immediately after insertion of chip into socket).
 - --All known data formats are supported. Automatic file format detection and conversion during loading of file.
 - --The rich-featured auto-increment function enables one to assign individual serial numbers to each programmed device - or simply increments a serial number, or the function enables one to read serial numbers or any programmed device identification signatures from a file.
 - --The software also provide a many information about programmed device. As a special, the drawing of all available packages are provided. The software provide also explanation of chip labelling (the meaning of prefixes and suffixes at the chips) for each supported chip.
 - --The software provide a full information for ISP implementation: Description of ISP connector pins for currently selected chip, recommended target design around in-circuit programmed chip and other necessary information.
 - --The remote control feature allows to be PG4UW software flow controlled by other application ?\$C either using .BAT file commands or using DLL file.
 - DLL file, examples (C/PAS) and manual are part of standard software delivery.
 - --Jam files of JEDEC standard JESD-71 are interpreted by Jam Player. Jam files are generated by design software which is provided by manufacturer of respective programmable device. Chips are programmer in-ZIF or through ISP connector (IEEE 1149.1 Joint Test Action Group (JTAG) interface).
 - --VME files are interpreted by VME Player. VME file is a compressed binary variation of SVF file and contains high-level IEEE 1149.1 bus operations. VME files are generated by design software which is provided by manufacturer of respective programmable device. Chips are programmer in-ZIF or through ISP connector (IEEE 1149.1 Joint Test Action Group (JTAG) interface).
 - --Multiple devices are possible to program and test via JTAG chain: JTAG chain (ISP-Jam) or JTAG chain (ISP-VME).

OBD2Repair

Web: www.obd2repair.com

Email: info@obd2repair.com

-
- --Attaching of more BeeProg programmers to the same PC (through USB port) is achieved a powerful multiprogramming system, which support as many chips, as are supported by BeeProg programmer and without obvious decreasing of programming speed. It is important to know, there is a concurrent multiprogramming - each programmer works independently and each programmer can program different chip, if necessary.

Specification

- Base unit, DACs
- --USB 2.0 port
- --FPGA based IEEE 1284 slave printer port, up to 1MB/s transfer rate
- --on-board intelligence: powerful microprocessor and FPGA based state machine
- --three D/A converters for VCCP, VPP1, and VPP2, controllable rise and fall time
- --VCCP range 0..8V/1A
- --VPP1, VPP2 range 0..26V/1A
- --autocalibration
- --selftest capability
- --protection against surge and ESD on power supply input, parallel port connection

ZIF socket, pindriver

- --48-pin DIL ZIF (Zero Insertion Force) socket accepts both 300/600 mil devices up to 48-pin
- --pindrivers: 48 universal
- --VCCP/VPP1/VPP2 can be connected to each pin
- --perfect ground for each pin
- --FPGA based TTL driver provides H, L, CLK, pull-up, pull-down on all pindriver pins
- --analog pindriver output level selectable from 1.8 V up to 26V
- --current limitation, overcurrent shutdown, power failure shutdown
- --ESD protection on each pin of socket (IEC1000-4-2: 15kV air, 8kV contact)
- --continuity test: each pin is tested before every programming operation

ISP connector

- --10-pin male type with missinsertion lock
- --5 TTL pindrivers, provides H, L, CLK, pull-up, pull-down; level H selectable from 1.8V up to 5V to handle all (low-voltage including) devices.
- --1x VCCP voltage (range 2V..7V/100mA), can be applied to pins 1, 3

OBD2Repair

Web: www.obd2repair.com

Email: info@obd2repair.com

- programmed chip voltage (VCCP) with both source/sink capability and voltage sense
- --1x VPP voltage (range 2V..25V/50mA), can be applied to pins 2,3,4,6,8,10
- --target system supply voltage (range 2V..6V/250mA)

DEVICE SUPPORT

Programmer, in ZIF socket

- --EPROM: NMOS/CMOS, 2708*, 27xxx and 27Cxxx series, with 8/16 bit data width, full support for LV series
- --EEPROM: NMOS/CMOS, 28xxx, 28Cxxx, 27EExxx series, with 8/16 bit data width
- --Flash EPROM: 28Fxxx, 29Cxxx, 29Fxxx, 29BVxxx, 29LVxxx, 29Wxxx, 49Fxxx
--series, from 256Kbit to 32Mbit, with 8/16 bit data width, full support for LV series
- Serial E(E)PROM: 24Cxxx, 24Fxxx, 25Cxxx, 45Dxxx, 59Cxxx, 25Fxxx, 25Pxxx, 85xxx, 93Cxxx, NVM3060, MDAxxx series, full support for LV series
- --Configuration (EE)PROM: XCFxxx, XC17xxxx, XC18Vxxx, EPCxxx, AT17xxx, 37LVxx
- --1-Wire E(E)PROM: DS1xxx, DS2xxx
- --PROM: AMD, Harris, National, Philips/Sigmetics, Tesla, TI
- --NV RAM: Dallas DSxxx, SGS/Inmos MKxxx, SIMTEK STKxxx, XICOR 2xxx, ZMD U63x series
- --PLD: Altera: MAX 3000A, MAX 7000A, MAX 7000B, MAX 7000S, MAX7000AE
- --PLD: Lattice: ispGAL22V10x, ispLSI1xxx, ispLSI1xxxEA, ispLSI2xxx, ispLSI2xxxA, ispLSI2xxxE, ispLSI2xxxV, ispLSI2xxxVE, ispLSI2xxxVL, LC4xxxB/C/V/ZC, M4-xx/xx, M4A3-xx/xx, M4A5-xx/xx, M4LV-xx/xx
- --PLD: Xilinx: XC9500, XC9500XL, XC9500XV, CoolRunner XPLA3, CoolRunner-II
- --other PLD: SPLD/CPLD series: AMI, Atmel, AMD-Vantis, Gould, Cypress, ICT, Lattice, NS, Philips, STM, VLSI, TI
- --Microcontrollers 48 series: 87x41, 87x42, 87x48, 87x49, 87x50 series
- --Microcontrollers 51 series: 87xx, 87Cxxx, 87LVxx, 89Cxxx, 89Sxxx, 89LVxxx, all **Manufacturers, Philips LPC series**
- --Microcontrollers Intel 196 series: 87C196 KB/KC/KD/KT/KR/...
- --Microcontrollers Atmel AVR: AT90Sxxxx, ATtiny, ATmega series
- --Microcontrollers Cypress: CY8Cxxxxx
- --Microcontrollers ELAN: EM78Pxxx
- --Microcontrollers MDT 1xxx and 2xxx series

-
- --Microcontrollers Microchip PICmicro: PIC10xxx, PIC12xxx, PIC16xxx, PIC17Cxxx, PIC18xxx, **DSPIC series**
 - --Microcontrollers Motorola (Freescale): 68HC05, 68HC08, 68HC11 series
 - --Microcontrollers Myson MTV2xx, 3xx, 4xx and 5xx series
 - --Microcontrollers National: COP8xxx series
 - --Microcontrollers NEC: uPD78Fxxx series
 - --Microcontrollers Scenix (Uicom): SXxxx series
 - --Microcontrollers SGS-Thomson: ST6xx, ST7xx, ST10xx series
 - --Microcontrollers TI: MSP430 and MSC121x series
 - --Microcontrollers ZILOG: Z86/Z89xxx and Z8xxx series
 - --Microcontrollers other: EM Microelectronic, Fujitsu, Goal Semiconductor, Hitachi, Holtek, Princeton, Macronix, Winbond, Infineon(Siemens), Samsung, Toshiba, ...

Programmer, through ISP connector

- --Serial E(E)PROM: IIC series, MW series, SPI series, KEELOQ series, serial data Flash, PLD configuration memories
- --Microcontrollers Atmel: AT89Sxxx, AT90Sxxxx, ATtiny, ATmega series
- --Microcontrollers Cypress: CY8C2xxxx
- --Microcontrollers Elan: EM78Pxxx, EM6xxx series
- --Microcontrollers EM Microelectronic: 4 and 8 bit series
- --Microcontrollers Microchip PICmicro: PIC10xxx, PIC12xxx, PIC16xxx, PIC17xxx, PIC18xxx, dsPIC series
- --Microcontrollers Motorola/Freescale: HC11 series, HC908 series (both 5-wire, All-wire)
- --Microcontrollers NEC: uPD7xxx series
- --Microcontrollers Philips: LPC2xxx series, LPC series, 89xxx series
- --Microcontrollers Scenix (Uicom): SXxxx series
- --Microcontrollers TI: MSP430 (both JTAG and BSL series), MSC12xxx series
- --PLD: Lattice: ispGAL22xV10x, ispLSI1xxxEA, ispLSI2xxxE, ispLSI2xxxV, ispLSI2xxxVE, ispLSI2xxxVL, M4-xx/xx, M4LV-xx/xx, M4A3-xx/xx, M4A5-xx/xx, LC4xxxB/C/V/ZC
- --Various PLD (also by JAM player/JTAG support):
- Altera: MAX 3000A, MAX 7000A, MAX 7000B, MAX 7000S, MAX 9000, MAX II
- Xilinx: XC9500, XC9500XL, XC9500XV, CoolRunner XPLA3, CoolRunner-II

Notes:

- --devices marked * are obsolete, programming with additional module
- --for all supported devices see actual DEVICE LIST

- I.C. Tester
 - TTL type: 54,74 S/LS/ALS/H/HC/HCT series
 - CMOS type: 4000, 4500 series
 - Static RAM: 6116 .. 624000
 - User definable test pattern generation

Package support

- --support all devices in DIP with default socket
- --package support includes DIP, SDIP, PLCC, JLCC, SOIC, SOP, PSOP, SSOP, TSOP, TSOPII, TSSOP, QFP, PQFP, TQFP, VQFP, QFN (MLF), SON, BGA, EBGA, FBGA, VFBGA, UBGA, CSP, SCSP etc.
- --support devices in non-DIP packages up to 48 pins with universal adapters
- --programmer is compatible with third-party adapters for non-DIP support

Programming speed

Notes:

- --It is important to know, we always use random numbers pattern for programming speed testing. Some our competitors use "sparse" pattern, where only few non-Blank data are programmed or are there are used data with only few 0 bits (FE, EF, etc.). This cheating approach can "decrease" programming time considerable. If you plan to compare, ask always which pattern they use.
- --The programming speed depends on PC speed only slightly.
- --If the programmer attached to PC through LPT port, the programming might take longer.

Device/ Size [bits] Operation /Time

- 1.M50FW080 (parallel Flash) 100000Hx8 (8 Mega) programming and verify 22 sec.
- 2.AM29DL323DB (parallel Flash) 208000Hx16 (32 Mega) programming and verify 31 sec.
- 3.AM29DL640 (parallel Flash) 400080Hx16 (64 Mega) programming and verify 61 sec.
- 4.AT45D081 (serial Flash) 108000Hx8 (16 Mega) programming and verify 41 sec.
- 5.AT89C51RD2 (microcontroller) 10000Hx8 programming and verify 15 sec.
- 6.PIC18LF452 (microcontroller) 4000Hx16 programming and verify 4 sec.
- Conditions: PC Pentium 4, 2.4 GHz, USB 2.0, Windows XP.

SOFTWARE

- --Algorithms: only manufacturer approved or certified algorithms are used. Custom algorithms are available at additional cost.
- --Algorithm updates: software updates are available regularly, approx. every 2 weeks, free of charge.
- --Main features: revision history, session logging, on-line help, device and algorithm information.

Device operations

1.standard:

- --intelligent device selection by device type, manufacturer or typed fragment of part name
- --automatic ID-based selection of EPROM/Flash EPROM
- --blank check, read, verify
- --program
- --erase
- --configuration and security bit program
- --illegal bit test
- --checksum
- --interpret the Jam Standard Test and Programming Language (STAPL), JEDEC standard JESD-71
- --interpret the VME files compressed binary variation of SVF files

2.security

- --insertion test, reverse insertion check
- --contact check
- --ID byte check

3.special

- --production mode (automatic start immediately after device insertion)
- --auto device serial number increment
- --statistic
- --count-down mode

Buffer operations

- --view/edit, find/replace
- --fill/copy, move, byte swap, word/dword split

OBD2Repair

Web: www.obd2repair.com

Email: info@obd2repair.com

- --checksum (byte, word)
- --print

File load/save

- --no download time because programmer is PC controlled
- --automatic file type identification/recognition

Supported file formats:

- --unformatted (raw) binary
- --HEX: Intel, Intel EXT, Motorola S-record, MOS, Exormax, Tektronix, ASCII-SPACE-HEX,, ASCII HEX
- --Altera POF, JEDEC (ver. 3.0.A), eg. from ABEL, CUPL, PALASM, TANGO PLD, OrCAD PLD, PLD Designer ISDATA, etc.
- --JAM (JEDEC STAPL Format), JBC (Jam STAPL Byte Code), STAPL (STAPL File) JEDEC standard JESD-71
- --VME (ispVME file VME2.0/VME3.0)

GENERAL:

- PC system requirements
- --Common, software related requirements
- --Programmer hardware related requirements:
 - --either one USB port, 2.0 compatible
 - --or one (parallel) printer port with nothing attached, the IEEE 1284 compatible printer port (ECP/EPP) on PCI bus recommended

Operation

- --operating voltage 15V..18V DC, max. 1A
- --power consumption max. 12W active, about 2W sleep
- --dimensions 160x190x42 mm (6.3x7.5x1.7 inch)
- --weight (without external adapter) 0.9kg (1.98 lb)
- --temperature 5°C ÷ 40°C (41°F ÷ 104°F)
- --humidity 20%..80%, non condensing

Package includes:

- --BeeProg programmer
- --switching power adapter 100..240V AC/15V DC/1A
- --connection cable PC-programmer, LPT port
- --connection cable PC-programmer, USB port
- --ISP cable

OBD2Repair

Web: www.obd2repair.com

Email: info@obd2repair.com

- --diagnostic POD for selftest of the programmer
- --anti-dust cover for ZIF socket
- --user manual
- --software
- --registration card
- --calibration test report
- --transport case

Additional services:

- --Keep Current - ELNEC sends to user the latest version of programmer software and updated user documentation (Keep-Current package)
- --AlgOR (Algorithms On Request) - add new supported devices on customer request